## HiStone

## Self-Checkout System | HS520M

## Key Features

- □ 27" True flat capacitive touch screen enhancing user experience
- Multi-modular design allowing for self-service or self-checkout customization to suit a variety of hospitality or retail environments
- □ Flexible operational scenarios; wall mount or floor stand
- The core module has an elegant and stylish frame made of aluminium alloy



QINGDAO HISTONE INTELLIGENT COMMERCIAL SYSTEM CO.,LTD. Wisdom Valley, No. 8 Shengshui Road, Laoshan District, Qingdao City, China Tel: +86 (532) 6606 9168 infopos@histonetec.com

MODEL		HS520M
Processor		Intel <sup>®</sup> Core™ Skylake-U, 6th Generation High-Performance CPU i3-6100U SOC 2.3GHz
Operating System		POS Ready 7 / Windows 7 / Windows 8.1 / Windows 10 / Linux
Memory		SO-DIMM DDR4 2166MHz 4GB up to 16GB
Storage		SATA SSD 128GB up to 256GB
Display Panel		27" TFT LCD   16:9   Standard resolution: 1920 x 1080
Touch Screen		True flat capacitive touch screen
Power Supply		150W (Integrated)
Speaker		2* 5W Speaker
I/O Ports	USB	4* 2.0
	Serial	2* DB9
	LAN	1* RJ45 100M/1000M Gigabit
Default Peripherals	Printer	Integrated 80mm thermal printer
	Scanner	Integrated: supports 1D/2D barcodes
	Microphone	Omnidirectional Mic
	Camera	Membership (higher resolution)
		Face ID (3D information for face recognition & payment
		Security Camera (24/7 access)
	Wi-Fi®	Dual-band 802.11a/b/g/n/ac 2.4GHz/5GHz
	MSR	3 tracks MSR
	RFID	MSR & RFID
	FPR	Fingerprint reader
	Indicator	Status indicator light
Optional Peripherals		Number plate
	Shelving	Small shelving unit (metal or plastic)
		Large shelving unit (metal or plastic)
	Stand	Floor stand
		Large metal plate for stability (no need for screws)
	Wall Mount	Wall mount bracket
	Bracket	EFTPOS holder
		Separate fiscal printer holder
		Disinfectant or sanitizer bottle holder
Dimensions (WxDxH)		1690 x 1092 x 482 mm
Weight		57kg (Core Module & Stand)

Disclaimer: All products specifications are subject to change without notice.



MODEL		HS520M
Operating Voltage		110 ~ 240VAC
Environment	Operating	5°C - 40°C / 40%-60% RH non-condensing
	Storage	-5°C - 50°C / 30%-80% RH non-condensing
EMC and Safety		CE/FCC Pending
Colour		Black or White

**Disclaimer:** All products specifications are subject to change without notice.



